
हॉट मिक्स एस्फाल्ट और बिटुमनी मकैडम
संयंत्रों के लिए तेल-ज्वलित रोटरी
शुष्कित्र — परीक्षण पद्धति
(पहला पुनरीक्षण)

**Oil-Fired Rotary Dryers for Hot Mix
Asphalt and Bituminous Macadam
Plants — Method of Test**
(*First Revision*)

ICS 91.220

© BIS 2023



भारतीय मानक ब्यूरो
BUREAU OF INDIAN STANDARDS
मानक भवन, 9 बहादुर शाह ज़फर मार्ग, नई दिल्ली - 110002
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI - 110002
www.bis.gov.in www.standardsbis.in

FOREWORD

This Indian Standard (First Revision) was adopted by the Bureau of Indian Standards, after the draft finalized by the Construction Plant and Machinery Sectional Committee had been approved by the Mechanical Engineering Division Council.

The output of a hot mix asphalt plant or a bituminous macadam plant is often determined by the output of its dryer under certain defined conditions. A need has, therefore, been felt to formulate a standard laying down an accepted basis for measuring the performance of the dryer unit under standardized conditions.

This standard was first published in 1969. This standard is being revised again to keep pace with the latest technological developments and international practices. In this revision, the standard has been brought into the latest style and format of Indian Standards, and references of Indian Standards, wherever applicable have been updated. BIS certification marking clause has been modified to align with the revised *Bureau of Indian Standards Act, 2016*.

This standard provides a method of testing oil-fired rotary dryers of both continuous and batch types under conditions of composition and temperature agreed to between the parties concerned.

When the user does not lay down particular conditions, the recommended test conditions given in Annex A may be used to cover the production of dense asphaltic concrete and bituminous macadam. These recommendations also form a basis upon which a manufacturer can state the output of oil-fired rotary dryers.

The composition of the committee responsible for the formulation of this standard is listed in Annex C.

In reporting the result of a test or analysis made in accordance with this standard, is to be rounded off, it shall be done in accordance with IS 2 : 2022 'Rules for rounding off numerical values (*second revision*)'.

Indian Standard

OIL-FIRED ROTARY DRYERS FOR HOT MIX ASPHALT AND BITUMINOUS MACADAM PLANTS — METHOD OF TEST

*(First Revision)***1 SCOPE**

1.1 This Indian Standard lays down the method for testing oil-fired rotary aggregate dryers of both continuous and batch types, and for reporting the results as given in Annex B.

1.2 Recommended test conditions corresponding to the requirements in the manufacture of dense asphaltic concrete and bituminous macadam are also included for use when special test conditions are not laid down, and as a basis upon which manufacturers may declare the output of dryers.

2 REFERENCES

The standard listed below contains provisions which through their reference in this text constitute provisions of this standard. At the time of publication, the editions indicated were valid. All standards are subject to revision and parties to agreements based on this standard is encouraged to investigate the possibilities of applying the most recent editions of the standard listed below.

<i>IS No.</i>	<i>Title</i>
IS 460 (Part 1) : 2020	Test sieves — Specification: Part 1 Wire cloth test sieves (fourth revision)

3 TERMINOLOGY

3.1 Conditions of Test — Before starting the test, the feed of the dryer shall be adjusted to the rated output of the plant and the following conditions of the test shall be approved:

- a) Type of aggregate to be used;
- b) Grading of aggregate;
- c) Moisture content in aggregate;
- d) Temperature at discharge; and
- e) Moisture content in aggregate after drying.

3.1.1 Where special test conditions are not laid down the recommended conditions of the test given in Annex A may be adopted for dryers to be used in the manufacture of rolled asphalt, coated macadam or fine cold asphalt.

3.2 Measurements Required — The following measurements shall be made:

- a) Output of aggregate in tonne per hour;

- b) Moisture content before and after drying;
- c) Temperature before and after drying;
- d) Grading of the aggregate before and after drying; and
- e) Fuel consumption in litres per hour and in litres per tonne of aggregate output.

NOTE — The temperature and humidity of the air shall be recorded and an indication given of the speed of the wind.

3.3 Duration of Test — The test period shall be at least 30 minutes. Immediately before the beginning of the test period the dryer shall be run under test conditions for at least 15 minutes, or for such longer time as may be required for stable conditions to be obtained. No variation in conditions shall be made during the period of the test except minor variations (made either manually or automatically) in burner settings to control the temperature.

3.4 Consistency of Aggregate Feed — Means shall be provided to maintain a constant composition and constant rate of feed throughout the test period. The ratio of material passing and retained on a 2.36 mm IS Sieve should be accurately controlled. A constant feed shall be maintained until the last test results have been recorded.

3.4.1 In testing batch dryers the time cycle shall be constant throughout the period of the test.

4 TEST PROCEDURE**4.1 Output**

4.1.1 The output shall normally be measured at the outlet of the dryer. Where practicable the entire quantity of aggregate dried during the test period shall be discharged as directly as possible into tared vehicles and weighed on an approved weighbridge.

4.1.2 When the test is carried out in the course of normal production or on large continuous dryers, where it is not convenient to weigh the whole output at least six measurements shall be made, taking the discharge for short periods only, at regular intervals. A tared container should be moved into position to catch the whole flow, or the flow diverted to such a container, for a period which can be accurately timed by a stop watch (for example, 10 set to 30 set according to the capacity of the dryer being tested). The rate of flow in tonnes per hour shall be calculated from the weight of the aggregate in the container.

4.2 Determination of Moisture Content

4.2.1 At least six samples of the aggregate shall be taken at approximately even intervals throughout the test period from both the feed and the discharge ends of the dryer. Where possible, quantities of about 25 kg shall be taken by catching the whole flow in a container inserted into the stream of material. Each of these batches shall be reduced on a sample splitter or 'quartered' to give a final sample of about 4.5 kg which shall be put into a suitable previously weighed container, for subsequent determination of the moisture content. Where possible, the sample and container shall be weighed immediately to obtain the weight of the sample and its moisture. Care shall be taken to minimize the loss of moisture, particularly from warm material, during the sampling procedure. If immediate weighing is not possible, then an air-tight container shall be used, such as a lever lid tin, and this container and its contents shall be weighed before unsealing. A balance capable of weighing up to 7 kg readable and accurate to 1.0 g shall be used.

4.2.2 The sample should be thoroughly dried either in a well-ventilated oven at 105 °C to 110 °C for 24 hours, or by heating over a burner in an open tray, with constant stirring, for 30 minutes after all visible evidence of moisture has disappeared. This method of drying should be repeated on the first sample to ensure that no further loss of weight occurs.

4.2.3 The moisture content of the sample is the difference between the initial and final dried weight expressed as a percentage of the final weight.

4.2.4 If the system of feeding the dryer is such that the above method of sampling would not give reasonably representative samples of mixed constituents at the feed end, then separate sets of samples shall be taken from each constituent of the feed, their moisture contents measured independently, and the average moisture content calculated from the ratios of the various constituents used in the mixed feed material.

4.2.4.1 This ratio may have to be estimated from the grading as referred to under 4.4.

4.3 Temperature Measurement

4.3.1 The thermometer used shall preferably be a metallic thermometer having a range appropriate to the temperature of the materials, say 0 °C to 100 °C for the feed materials, and 0 °C to 260 °C for the discharge, and their thermal capacity should not exceed that of a mercury-in-glass thermometer of about 6 mm diameter.

4.3.2 Feed Temperature

When the feed is from open stock piles, two or three readings of input temperature (measured by inserting a thermometer deeply into the heap) will

be adequate. If there is reason to expect variations in feed temperature, for example, when feeding from bulk storage bins of pre-dried material, then samples should be taken by the same method and of the same frequency as given in 4.3.2 for the outlet temperature determination.

4.3.3 Outlet Temperature

4.3.3.1 Temperature measurements shall be made on the aggregate, leaving the dryer at regular intervals during the period of the test, so that at least six results are obtained during the period of the test. The samples shall be taken by inserting a lagged container into the stream of aggregate, leaving the dryer so as to catch the whole flow for a period sufficient to collect about 9 kg to 13.5 kg of material. A lid shall be placed on the lagged container and the aggregate inside shall be mixed gently at intervals for five minutes to allow the temperature of the different particle sizes to even out; the temperature shall then be determined. A can (of diameter 4 to 6 times the maximum size of the aggregate and depth equal to twice the diameter) may be used on asphaltic materials where the sand content is greater than 50 percent.

NOTE — Before taking the first sample, the container should be brought to temperature by taking a few trial samples before the start of the test period.

4.3.3.2 The thermometer used for the discharge temperature should be kept in some of the hot materials of each batch till the following batch is ready.

4.4 Grading of Aggregate

4.4.1 During the process of quartering the batches referred to in 4.2, a sufficient quantity shall be retained from each batch for drying and sieving in accordance with IS 460 (Part 1). The sample dried for determination of moisture content, if and of adequate size, may be used for this grading.

4.4.1.1 If two or more constituents of the aggregate are fed in sequence through the same feed hopper, samples taken as described in 4.2 may not be representative of the mixed feed materials. In such cases, accurate sieve analysis of the feed cannot be made. An approximation should be made by taking sets of samples, each set comprising a sample of each constituent of the feed as brought to the feed hopper.

4.4.1.2 These samples should be graded separately and the composite grading obtained by combining the results in the proportions of each constituent used in the feed. If this result is not in reasonable agreement with the grading of the discharged materials, then combinations of different proportions of the constituent grading's should be tried, until ratios are found which give a composite grading as close as possible to that of the discharged

materials. The proportions so found shall be taken as those of the feed material for the purposes of estimation of the moisture content in 4.2.

4.5 Oil Consumption

4.5.1 The total quantity of oil used during the test period shall be measured to an accuracy of ± 2.5 percent. Where possible, a small service fuel tank mounted on a scale, or so connected that it can be weighed or measured accurately by dipping at the beginning and end of the test period, should be used, and the quantity of oil burned calculated from the difference in readings.

4.5.2 Alternatively, the oil level in the main tank should be measured at the beginning and end of the period. The duration should be such that the change of level is at least 40 mm and the measurement should be made to an accuracy of 51 mm. If a change of level as indicated is not achieved, a service tank shall be fitted. All other conditions affecting the

level shall be the same at the beginning and end of the period. If the tank is of such a shape that the surface area of the oil can be accurately measured, and does not vary appreciably between the two levels, then the quantity can be calculated from the change of level.

4.5.2.1 If the tank shape is irregular, the quantity shall be measured indirectly. When the burners are off, the level shall be restored to the initial position. Oil shall then be drawn off into separate containers, in which it can be measured until the level in the tank falls to the lower test level. The quantity drawn off shall be taken as the consumption during the test. In some circumstances, it may be more convenient to add a measured quantity of oil to raise the level in the tank from the lower to the higher test level.

4.5.3 The oil consumption shall be expressed in litres per hour, and in litres per tonne of aggregate dried, the type, calorific value and specific gravity of oil used being specified.

ANNEX A
(Foreword and Clause 3.1.1)

RECOMMENDED CONDITIONS OF TEST (FOR USE WHEN SPECIAL CONDITIONS ARE NOT LAID DOWN)

A-1 RECOMMENDED CONDITIONS OF TEST

When special conditions of test are not laid down, use of the conditions given in Table 1 are recommended to cover the production of rolled asphalt, coated macadam, and fine cold asphalt.

Table 1 Recommended Conditions of Test
(Clause A-1)

Feed:	DENSE ASPHALTIC CONCRETE			BITUMINOUS MACADAM		
a) Type of aggregate	Crushed rock or gravel			Crushed rock or gravel		
b) Grading	IS Sieve Designation	Percentage passing by weight	Tolerance percent	IS Sieve Designation	Percentage passing by weight	Tolerance percent
	20 mm	100	± 5	40 mm	100	± 5
	12.5 mm	90	± 5	25 mm	85	± 5
	10 mm	80	± 5	20 mm	68	± 5
	4.75 mm	60	± 5	10 mm	37.5	± 5
	2.36 mm	42.5	± 2	4.75 mm	20	± 5
	600 micron	23.5	± 2	2.36 mm	12.5	± 2
	300 micron	18	± 2	75 micron	2	± 2
	150 micron	12	± 2			
	75 micron	7	± 2			
c) Temperature	Not less than 5 °C			Not less than 5 °C		
d) Moisture content	5 percent to 6 percent by weight (of dry materials)			5 percent to 6 percent by weight (of dry materials)		
Discharge:						
a) Temperature	175 °C to 200 °C			Damp condition not more than 80 °C Wet condition not more than ¹⁾ 110 °C		
b) Moisture content	Not more than 0.25 percent by weight (of dry materials)			Not more than 0.25 percent by weight (of dry materials)		
¹⁾ Should material originally in a wet condition be required to have an outlet temperature less than 110 °C , then a cooling unit or other special method would be required.						

ANNEX B
(Clause 1.1)

B-1 TYPICAL FORM FOR RECORDING RESULTS OF TEST ON OIL-FIRED ROTARY DRYER

Date.....

Dryer by (manufacturer's name).....

Type of dryer (batch or continuous).....

- a) Length of dryer
- b) Length of flame
- c) Type of lining

Main duty:

Preparation of aggregates for : Dense asphaltic concrete
Bituminous macadam
Special conditions (give details)

Rated output with damp/wet feed..... tonne per hour

Test Conditions:

Air temperature °C Humidity

Wind conditions (if dryer tested in the open)

Type of aggregate (trade group).

Approximate grading of aggregate (to IS: or give percentage passing main sieves)

Fine aggregate/coarse aggregate ratio (for asphalt dryer).

If coupled to dust collector, state type

Position of burner in use (where alternative positions are available).....

Test Records:

Start of test run hours min

End of test run hours..... min

Approximate time running before start of test..... hours..... min

Duration of test run min.....

Feed materials, average temperature..... °C

Time each charge is dryer (batch dryers) min

Approximate time of passage of material (continuous dryers). min

Angle of inclination to horizontal.....°

Speed of dryer.....rev/min

Feed Materials						
Sample No.	1	2	3	4	5	6
Time taken – minimum from start						
Temperature °C						
Moisture content percentage of dry weight						
Grading: Percentage retained/passing						
IS Sieve:						
40 mm						
25 mm						
20 mm						
12.5 mm						
10 mm						
4.75 mm						
2.36 mm						
600 micron						
300 micron						
150 micron						
75 micron						

IS 5436 : 2023

Type of thermometer used for feed material

Method of sampling and taking temperature

Discharged Materials						
Sample No.	1	2	3	4	5	6
Time taken – minimum from start						
Temperature °C						
Moisture content percentage of dry weight						
Grading: Percentage retained/passing						
IS Sieve:						
40 mm						
25 mm						
20 mm						
12.5 mm						
10 mm						
4.75 mm						
2.36 mm						
600 micron						
300 micron						
150 micron						
75 micron						

Type of thermometer used for discharge material

Method of sampling and taking temperature

Average feed temperature..... °C

Average discharge temperature..... °C

Average rise in temperature °C

Average moisture content in feed.....percent

Average moisture content in discharge..... percent

Average reduction in moisture content.....percent

Total output during test run tonne kg

Method of estimating output.....

Rate per hour tonne kg

Calorific value of fuel used..... kilocalories/kg (or kilocalories/litre)

Specific gravity of fuel used.....

Fuel burned during test run..... litre

Fuel consumption per hour..... litre

Fuel consumption per tonne of aggregate litre

ANNEX C
(Foreword)

COMMITTEE COMPOSITION

Construction Plant and Machinery Sectional Committee, MED 18

<i>Organization</i>	<i>Representative(s)</i>
Directorate General of Quality Assurance, Ministry of Defence, New Delhi	BRIG. RAJNEESH BHATNAGAR (Chairperson)
AIMIL Limited, New Delhi	SHRI ROHITASH BARUA SHRI K. K. VYASAS (<i>Alternate</i>)
Ajax Engineering Private Limited, Bengaluru	SYED MOHAMMED RIAZ NAWAZ SHRI JORLIN P. V. (<i>Alternate I</i>) SHRI MANJUNATH D. JAGGAL (<i>Alternate II</i>) SHRI KRISHNA KISHORE (<i>Alternate III</i>)
Ammann Apollo India Private Limited, Jagudan, Gujarat	SHRI GIRISH DIXIT SHRI ASHISH PATEL (<i>Alternate I</i>) SHRI MANAN RAJPURA (<i>Alternate II</i>) SHRI PRASAD DAYAL (<i>Alternate III</i>) SHRI GEETESH MAKADIA (<i>Alternate IV</i>) SHRI ARPAN PATEL (<i>Alternate V</i>) SHRI KARTIK TRIVEDI (<i>Alternate VI</i>)
Atlas Copco India Limited, Pune	SHRI VIJAY SHARMA SHRI YOGESH TULJAPURKAR (<i>Alternate</i>)
B. G. Shirke Construction Technology Limited, Pune	SHRI A. D. BHOSALE SHRI SUNIL KEDAR (<i>Alternate</i>)
Builders Association of India, Mumbai	SHRI V. G. SAKTHIKUMAR
Caterpillar India Private Limited, Chennai	SHRI K. REJI JOSE SHRI RAMESH VISHWANATHAN (<i>Alternate</i>)
Central Water Commission, New Delhi	SHRI DILIP KUMAR JHA SHRI KRISHNAJI SINGH (<i>Alternate</i>)
CSIR - Central Building Research Institute, Roorkee	DR SUVIR SINGH DR BANTI A. GEDAM (<i>Alternate</i>)
Directorate General Border Roads, New Delhi	COL AMIT BHARDWAJ
Directorate General of Quality Assurance, Ministry of Defense, New Delhi	COL RAVI LOGANATHAN LT COL S. TALEWAR (<i>Alternate</i>)
Epiroc Mining India Limited, Nashik	SHRI VENKATESAN BASHYAM SHRI MUTTANNA JAPANNAVAR (<i>Alternate</i>)
Escorts Construction Equipment Limited, Faridabad	SHRI FAIZ AHMAD SHRI ASHOK CHAUHAN (<i>Alternate I</i>) SHRI LAXMI CHAND TYAGI (<i>Alternate II</i>)
Indian Construction Equipment Manufacturers Association, New Delhi	SHRI K. V. KRISHNAMURTHY
IRCON International Limited, New Delhi	SHRI RANDHIR GUPTA SHRI S. K. RAY (<i>Alternate</i>)
Jaypee India Limited, Kolkata	SHRI KUMAR M. MEHTA SHRI RAHUL KUMAR TEOTIA (<i>Alternate</i>)
John Deere India Private Limited, Mumbai	SHRI KARTHIK KALIAPPAN SHRI RAJ ANAND (<i>Alternate</i>)

<i>Organization</i>	<i>Representative(s)</i>
Larsen and Toubro Construction Limited, Karnataka	SHRI GURUPRASAD S. R. SHRI DHANAJI HARIBA MANGUDE (<i>Alternate</i>)
Larsen and Toubro Limited, Mumbai	SHRI K. KESHAVA SHRI M. SURESH KUMAR (<i>Alternate</i>)
Ministry of Road Transport and Highways, New Delhi	SHRI K. C. SHARMA SHRI JITENDRA KUMAR (<i>Alternate</i>)
National Council for Cement and Building Materials, Faridabad	SHRI KAPIL KUKREJA SHRI SAURABH BHATNAGAR (<i>Alternate</i>)
Schwing Stetter (India) Private Limited, New Delhi	SHRI RAJEEV SHALIA SHRI VARADHARAJAN R. (<i>Alternate</i>)
Volvo Construction Equipments India Private Limited, Bengaluru	SHRI V. R. SAI PRASAD POLIPALLI SHRI K. RAGHURAMAN (<i>Alternate</i>)
Wirtgen India Private Limited, Pune	SHRI DEEPAK BHOIR SHRI PARUL ARORA (<i>Alternate</i>)
In Personal Capacity (<i>Flat no. 3052, Prestige Shantiniketan, Whitefield Main Road, Bengaluru</i>)	SHRI S. N. MAHAJAN
In Personal Capacity (<i>D-24, Amar Colony, New Delhi</i>)	SHRI SATENDER KUMAR
BIS Directorate General	SHRI RAJNEESH KHOSLA, SCIENTIST 'F'/SENIOR DIRECTOR AND HEAD (MECHANICAL ENGINEERING) [REPRESENTING DIRECTOR GENERAL (<i>Ex-officio</i>)]

Member Secretary
SHRI LOKRAJ MEENA
SCIENTIST 'B'/ASSISTANT DIRECTOR
(MECHANICAL ENGINEERING), BIS

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 2016* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Head (Publication & Sales), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the website- www.bis.gov.in or www.standardsbis.in.

This Indian Standard has been developed from Doc No.: MED 18 (2013).

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002

Telephones: 2323 0131, 2323 3375, 2323 9402

Website: www.bis.gov.in

Regional Offices:

	Telephones
Central : 601/A, Konnectus Tower -1, 6 th Floor, DMRC Building, Bhavbhuti Marg, New Delhi 110002	{ 2323 7617
Eastern : 8 th Floor, Plot No 7/7 & 7/8, CP Block, Sector V, Salt Lake, Kolkata, West Bengal 700091	{ 2367 0012 2320 9474
Northern : Plot No. 4-A, Sector 27-B, Madhya Marg, Chandigarh 160019	{ 265 9930
Southern : C.I.T. Campus, IV Cross Road, Taramani, Chennai 600113	{ 2254 1442 2254 1216
Western : Plot No. E-9, Road No.-8, MIDC, Andheri (East), Mumbai 400093	{ 2821 8093

Branches : AHMEDABAD. BENGALURU. BHOPAL. BHUBANESHWAR. CHANDIGARH. CHENNAI. COIMBATORE. DEHRADUN. DELHI. FARIDABAD. GHAZIABAD. GUWAHATI. HIMACHAL PRADESH. HUBLI. HYDERABAD. JAIPUR. JAMMU & KASHMIR. JAMSHEDPUR. KOCHI. KOLKATA. LUCKNOW. MADURAI. MUMBAI. NAGPUR. NOIDA. PANIPAT. PATNA. PUNE. RAIPUR. RAJKOT. SURAT. VISAKHAPATNAM.